

Material Safety Data Sheet

Section I Company Information

Product Name: **Reliable BD40**

Company Name: Reliable Solutions Inc.
 Address: 524 Morse Ave. Schaumburg, IL. 60193
 Phone: 800/656-7774
 Emergency Phone: 800/535-5053

Proper Shipping Name: Corrosive Liquids, nos (Contains Caustic Soda)
 Identification No: UN 1760
 Hazard Class: Class 8
 Generic Description: Cleaning Compound

Section II Hazardous Ingredients

CAS No	Ingredient	%	TLV
1310-73-2	Caustic Soda	2-5	2 mg/M3
26027-38-3	Nonionic Surfactant	10-20	
111-76-2	EG Butyl Ether	15-25	25 ppm

Section III Physical Data

Boiling Point: 212 F Specific Gravity: 1.01
 Vapor Pressure: Not Determined Percent Volatile: NA
 Vapor Density: Less than Air H2O Solubility: Complete
 Evaporation Rate: Slower than n-Butyl Acetate
 Appearance & Odor: Clear Solution, Typical Mild odor

Section IV Fire & Explosion Data

Flash Point: None
 Extinguishing Media: Foam or carbon dioxide or dry chemical.
 Firefighting Procedure: Wear self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode when fighting fires.

Section V Health Hazard Data

Routes of Entry: Inhalation, Skin & Ingestion
Eyes: Can cause mild to moderate irritation. **Skin:** Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis. **Breathing:** Excessive inhalation of vapors can cause nasal and respiratory irritation. Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.
First Aid Procedures:
Eyes: Irrigation of the eye immediately with water for ten minutes is good safety practice. **Skin:** Wash off in flow water or shower. Wash clothing before reuse.
Inhalation: Remove to fresh air if effects occur. If respiration stops, give mouth-to-mouth resuscitation. Administer oxygen if available. Call physician and/or transport to medical facility. **Ingestion:** Seek medical attention. Unless advised otherwise, induce vomiting by giving either syrup of ipecac followed by 2 glassed of water or by sticking finger down throat. Do not give anything by mouth if the person is drowsy, unconscious or has no gag reflex.

Section VI Reactivity Data

Hazardous Polymerization: Will not occur
 Stability: Stable
 Incompatibility: Avoid strong oxidizing agents.

Section VII Spill & Leak Procedures

Response to spills: Stop discharge, if it can be performed safely, and contain material. If a substantial quantity is spilled, recover with pump or vacuum. Otherwise, use an absorbent material. Place contaminated material in a suitable container for disposal. Do not flush to sewer, stream or other bodies of water.

Section VIII Protective Equipment

Respiratory Protection: If TLV of the product or any component is exceeded, a NIOSH/MSHA jointly approved air supplied respirator is advised. Engineering or administrative controls should be implemented to reduce exposure.
 Ventilation: Provide sufficient ventilation to maintain exposure below TLV(s).
 Protective Gloves: Wear chemical resistant gloves such as nitrile rubber.
 Eye Protection: Chemical splash goggles are advised.
 Other Protective Equipment: Wear impervious clothing and boots.


Section IX Special Precautions

Precautions to be taken in Handling and storage: Handle with reasonable care. Avoid breathing vapors. Store in a cool dry place. Dispose of empty containers in accordance with local, state and federal guidelines. This product contains Caustic Soda and Ethylene Glycol Monobutyl Ether which is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372.

Warranty Information - Please Read Carefully:

Reliable Solutions Inc. believes that the information in this literature is an accurate description of the typical characteristics and/or uses of the product, but it is your responsibility to thoroughly test the product in your specific application to determine its performance, efficacy and safety. Reliable Solutions Inc. provides the sole warranty that the product will meet our current sales specifications. Your exclusive remedy and Reliable Solutions Inc. only liability for breach or warranty is limited to refund of the purchase price or replacement of any product shown to be other than as warranted, and Reliable Solutions Inc. expressly disclaims any liability for incidental or consequential damages.

Revised: 4/12/2006



CORROSIVE LIQUID, N.O.S.
 (CONTAINS CAUSTIC SODA)
 CLASS 8, UN 1760, PACKING GROUP III